







Amount of plates ***	8	10	14	20	24	30	34	40	44	50
Volume Side 1 (l) *	0,21	0,28	0,42	0,63	0,77	0,98	1,12	1,33	1,47	1,68
Volume Side 2 (l) *	0,28	0,35	0,49	0,70	0,84	1,05	1,19	1,40	1,54	1,75
Max working pressure (bar)	16									
Min / Max temperature (°C)	-20 / +150									
PED Class Group 1 (Category) **	SEP									I
PED Class Group 2 (Category) **	SEP									
Plate packet depth L(mm) *	30,42	34,90	43,86	57,30	66,26	79,70	88,66	102,10	111,06	124,50
Net Weight Empty (kg)	1,84	2,10	2,62	3,40	3,92	4,70	5,22	6,00	6,52	7,30
Heat Transfer Area (m²)	0,26	0,35	0,53	0,79	0,97	1,23	1,41	1,67	1,85	2,11

* Calculated values (final tolerance to ISO 2768-m)
** PED Category IV (Available as special order or III with reduced max working pressure - please contact the sales team)
*** intermediate sizes on request

Where appropriate the following European standards and regulations were used during design and construction:

PED 2014/68/EU (Pressure Equipment Directive)
EN 1148 (Water to water heat exchangers for district heating)
EN 10272 (Stainless steel bars used for pressure purposes)
EN 10028-7 (Stainless steel flat products used for pressure purposes)
Please ask your sales partner if you require other standards or certification to be applied.

EN 13445 (Unfired Pressure Vessels)
ISO 2768-m (General tolerances class"m")
ISO 228-1 ("G" Thread BSP parallel)

©2025 Errors, Omissions and Technical Alterations excepted

Sizes in mm unless otherwise shown

Connections : 1.4301 (304) / Plates : 1.4404 (316L)

Cu-Free version also available

UNEX HEAT EXCHANGERS
UNEX Heatexchanger Engineering GmbH
Lobäckerstraße 60d
A-7000
Eisenstadt
Austria
www.unex.at
info@unex.at
Tel: + 43 (0) 2682 635 85 0
Fax: + 43 (0) 2682 635 85 20

Status	Change	Date	Name		Date	Name
				Drawn by	25.03.2025	HET
				Checked by		
				Updated by		

UniBraz PB14H-eco