








Amount of plates ***	8	10	14	20	24	30	34	40	44	50
Volume Side 1 (l) *	0,09	0,12	0,18	0,27	0,33	0,42	0,48	0,57	0,63	0,72
Volume Side 2 (l) *	0,12	0,15	0,21	0,30	0,36	0,45	0,51	0,60	0,66	0,75
Max working pressure (bar)	31									
Min / Max temperature (°C)	-196 / +200									
PED Class Group 1 (Category) **	SEP									
PED Class Group 2 (Category) **	SEP									
Plate packet depth L(mm) *	27,92	32,40	41,36	54,80	63,76	77,20	86,16	99,60	108,56	122,00
Net Weight Empty (kg)	1,33	1,45	1,69	2,05	2,29	2,65	2,89	3,25	3,49	3,85
Heat Transfer Area (m²)	0,11	0,14	0,22	0,32	0,40	0,50	0,58	0,68	0,76	0,86

* Calculated values (final tolerance to ISO 2768-m)
** PED Category IV (Available as special order or III with reduced max working pressure - please contact the sales team)
*** intermediate sizes on request

Where appropriate the following European standards and regulations were used during design and construction:

PED 2014/68/EU (Pressure Equipment Directive)
EN 1148 (Water to water heat exchangers for district heating)
EN 13445 (Unfired Pressure Vessels)
EN 10272 (Stainless steel bars used for pressure purposes)
ISO 2768-m (General tolerances class"m")
EN 10028-7 (Stainless steel flat products used for pressure purposes)
ISO 228-1 ("G" Thread BSP parallel)
Please ask your sales partner if you require other standards or certification to be applied.

©2025 Errors, Omissions and Technical Alterations excepted

Sizes in mm unless otherwise shown

Connections : 1.4301 (304) / Plates : 1.4404 (316L)

Cu-Free version also available

UNEX Heatexchanger Engineering GmbH
Lobäckerstraße 60d
A-7000
Eisenstadt
Austria
www.unex.at
info@unex.at
Tel: + 43 (0) 2682 635 85 0
Fax: + 43 (0) 2682 635 85 20

Status	Change	Date	Name

	Date	Name
Drawn by	25.03.2025	HET
Checked by		
Updated by		

PB6H