








Amount of plates ***	10	16	20	26	30	36	40	50	60	70	80
Volume Side 1 (l) *	0,07	0,13	0,16	0,22	0,25	0,31	0,34	0,43	0,52	0,61	0,70
Volume Side 2 (l) *	0,09	0,14	0,18	0,23	0,27	0,32	0,36	0,45	0,54	0,63	0,72
Max working pressure (bar)	25										
Min / Max temperature (°C)	-196 / +180										
PED Class Group 1 (Category) **	SEP										
PED Class Group 2 (Category) **	SEP										
Plate packet depth L(mm) *	16,50	22,20	26,00	31,70	35,50	41,20	45,00	54,50	64,00	73,50	83,00
Net Weight Empty (kg)	0,99	1,28	1,47	1,76	1,95	2,24	2,43	2,91	3,39	3,87	4,35
Heat Transfer Area (m²)	0,17	0,29	0,38	0,50	0,59	0,71	0,80	1,01	1,22	1,43	1,64

* Calculated values (final tolerance to ISO 2768-m)
** PED Category IV (Available as special order or III with reduced max working pressure - please contact the sales team)
*** intermediate sizes on request

Where appropriate the following European standards and regulations were used during design and construction:

PED 2014/68/EU (Pressure Equipment Directive)
EN 1148 (Water to water heat exchangers for district heating)
EN 10272 (Stainless steel bars used for pressure purposes)
EN 10028-7 (Stainless steel flat products used for pressure purposes)
EN 13445 (Unfired Pressure Vessels)
ISO 2768-m (General tolerances class“m”)
ISO 228-1 (“G” Thread BSP parallel)
Please ask your sales partner if you require other standards or certification to be applied.

©2025 Errors, Omissions and Technical Alterations excepted

Sizes in mm unless otherwise shown

Connections : 1.4301 (304) / Plates : 1.4404 (316L)

Cu-Free version also available

UNEX HEAT EXCHANGERS
UNEX Heatexchanger Engineering GmbH
Lobäckerstraße 60d
A-7000
Eisenstadt
Austria
www.unex.at
info@unex.at
Tel: + 43 (0) 2682 635 85 0
Fax: + 43 (0) 2682 635 85 20

Status	Change	Date	Name		Date	Name
				Drawn by	25.03.2025	HET
				Checked by		
				Updated by		

PBF9H