







Amount of plates ***	10	16	20	26	30	36	40	50	60	70
Volume Side 1 (l) *	0,06	0,11	0,14	0,19	0,22	0,27	0,30	0,38	0,46	0,54
Volume Side 2 (l) *	0,08	0,13	0,16	0,21	0,24	0,29	0,32	0,40	0,48	0,56
Max working pressure (bar)	10									
Min / Max temperature (°C)	-10 / +180									
PED Class Group 1 (Category) **	SEP									
PED Class Group 2 (Category) **	SEP									
Plate packet depth L(mm) *	16,35	22,05	25,85	31,55	35,35	41,05	44,85	54,35	63,85	73,35
Net Weight Empty (kg)	0,91	1,18	1,36	1,63	1,81	2,08	2,26	2,71	3,16	3,61
Heat Transfer Area (m²)	0,17	0,29	0,38	0,50	0,59	0,71	0,80	1,01	1,22	1,43

* Calculated values (final tolerance to ISO 2768-m)
** PED Category IV (Available as special order or III with reduced max working pressure - please contact the sales team)
*** intermediate sizes on request

Where appropriate the following European standards and regulations were used during design and construction:

PED 2014/68/EU (Pressure Equipment Directive)
EN 1148 (Water to water heat exchangers for district heating)
EN 10272 (Stainless steel bars used for pressure purposes)
EN 10028-7 (Stainless steel flat products used for pressure purposes)
Please ask your sales partner if you require other standards or certification to be applied.

EN 13445 (Unfired Pressure Vessels)
ISO 2768-m (General tolerances class"m")
ISO 228-1 ("G" Thread BSP parallel)

©2025 Errors, Omissions and Technical Alterations excepted

Sizes in mm unless otherwise shown

Connections : 1.4301 (304) / Plates : 1.4404 (316L)

UNEX HEAT EXCHANGERS
UNEX Heatexchanger Engineering GmbH
Lobäckerstraße 60d
A-7000
Eisenstadt
Austria
www.unex.at
info@unex.at
Tel: + 43 (0) 2682 635 85 0
Fax: + 43 (0) 2682 635 85 20

Status	Change	Date	Name

	Date	Name
Drawn by	25.03.2025	HET
Checked by		
Updated by		

UniBraz PBPF8H